

TECHNICAL DATASHEET

PLAKA

PLAKA SOFT PINBOARD

Absorption panel in polyester fibers, inserted in a frame and covered with a fabric

REF 12.12.32 - Version V01 - 24/08/2020



Description



PLAKA SOFT PINBOARD acoustic murals comprise of Plaka Soft boards with a visible aluminium frame for wall mounting.

Plaka Soft is an acoustic membrane made of 100% PET staple fibre. Recycled PET bottles are used to manufacture this product, for instance. The fibres are thermally and mechanically strengthened without the use of chemical binding agents.

Product class I is achieved for baby articles in accordance with the Oeko-Tex Standard 100. A special process is used to smoothen and compact the surface on both sides. This lends the membrane panels inherent rigidity, for use also as ceiling panels, for instance.

Plaka Soft features a broad spectrum of attractive properties.

The excellent attributes are:

- high level of sound absorption capability
- low weight
- good elasticity and stability of the Plaka Soft polyester board, which makes it perfectly adapted to a "pinboard" application.

The surrounding aluminium frame has a standard depth of 35mm and a viewing width of 8mm. Two adjustable screw hooks are foreseen on the back of the frame for simple attachment on the wall. Plaka Soft absorber boards with fabric cover (thickness 25mm) are used as filling. The fabric cover can be chosen from a wide range of colours and textures, making the acoustic mural PLAKA SOFT PINBOARD a design feature for functional wall areas that can drastically reduce both reverberation time and sound level.



©Copyright protected

This sheet, written with great care, supersedes all previous versions. The technical information on the design, models, illustrations, design values and specifications are believed to be accurate. We make no warranties (expressed or implied) as to its accuracy and assumes no liability in connection with non suitable use of this product. We reserve the right to modify the contents of this form without prior notice.



TECHNICAL DATASHEET



PLAKA SOFT PINBOARD

Absorption panel in polyester fibers, inserted in a frame and covered with a fabric

REF 12.12.32 - Version V01 - 24/08/2020



Application fields


PLAKA SOFT PINBOARD can be applied as a mural in:

- office and administration buildings, e.g. meeting rooms...
- kindergartens and schools
- shops
- call centres
- banks and insurance companies
- ..

Properties

Mechanical properties	
Base material	Plaka Soft – 100% polyester fibres White (colourless) and odourless flat polyester fibre textile material With a special method, we can dye Plaka Soft in diverse colour hues, according to RAL, for instance, or cover Plaka Soft with a coloured fabric.
Solubility	Not soluble in fat or water
Thermal conductivity	≥ 0.035 W/mK in acc. With DIN EN 12667
Fire behavior : • Polyester fibre textile material Plaka Soft : • Fabric cover :	B1 – flame resistant in acc. with DIN 4102 B1 – flame resistant in acc. with DIN 4102
Weight per unit area	25 mm panel, 1200 g/m ² (smoothened both sides) 50 mm panel, 2500 g/m ² (smoothened both sides) 200 mm panel, 5000 g/m ² (not smoothened)

Sound absorption of Plaka Soft boards in reverberation chamber as per DIN EN ISO 354.



©Copyright protected

This sheet, written with great care, supersedes all previous versions. The technical information on the design, models, illustrations, design values and specifications are believed to be accurate. We make no warranties (expressed or implied) as to its accuracy and assumes no liability in connection with non suitable use of this product. We reserve the right to modify the contents of this form without prior notice.

France: info.plaka.fr@leviat.com / +33 (0) 5 34 25 54 82



TECHNICAL DATASHEET


PLAKA

PLAKA SOFT PINBOARD

Absorption panel in polyester fibers, inserted in a frame and covered with a fabric

REF 12.12.32 - Version V01 - 24/08/2020





Important notice:

Above information are based on best present knowledge of current technology, but do not guarantee faultless processing of our products. The information is based on practical results of our tests, but is not binding and does not constitute warranties of characteristics in terms of Federal Supreme Court jurisdiction. Our information does not constitute a legally binding assurance of certain properties or suitability for a specific purpose. Supplementary information by our specialists are merely recommendations, for which no liability is accepted.

Due to the many possible applications of our products, we recommend subjecting the project to a thorough suitability test on original materials before release for further application.

Since our information are non-binding we do not warranty their correctness. For this reason we accept no liability for possible improper processing based on information submitted by our employees.

This technical data sheet replaces all previous versions and is valid until a new version is issued, or until Dec. 31, 2015. Please request the latest version after Jan. 01, 2016

Dimensions

Plaka Soft Pinboard dimensions	
Frame depth:	35 mm
Length and width:	500 x 1000 mm
	1000 x 1000 mm
	1000 x 1500 mm
	1000 x 2000 mm

We will be pleased to provide other dimensions on request.